

**DEFY**  
**ZERO G**



**18.9000.8812/79.M9000**

## MODEL SPECIFICATIONS

### KEY POINTS

New entirely skeletonised movement : El Primero 8812 S  
 "Gravity Control" gyroscopic module that ensures horizontal positioning of the regulating organ  
 Now occupies only 30% of its initial volume  
 Inspired by the legendary marine chronometers  
 Openworked dial

### MOVEMENT

Movement	El Primero 8812 S, Manual
Calibre	16 3/4 ` ` ` (Diameter: 38.5 mm)
Movement thickness	7.85 mm
Components	324
Components 2	Gyroscopic carriage made of 139 components
Jewels	41
Frequency	36,000 VpH (5 Hz)
Power-reserve	min. 50 hours
Finishes	Platinum counterweight of the gyroscopic system

### FUNCTIONS

Hours and minutes excentred at 12 o'clock  
 Small seconds at 9 o'clock  
 Self-regulating Gravity Control module at 6 o'clock  
 Power-reserve indication at 2 o'clock

### CASE, DIAL & HANDS

Diameter	44 mm
Diameter opening	35.5 mm
Thickness	14.85 mm
Crystal	Domed sapphire crystal with anti-reflective treatment on both sides
Case-back	Transparent sapphire crystal
Material	Rose gold 18-ct Rose Gold
Water-resistance	10 ATM
Dial	Openworked with one different-coloured counter

**DEFY**  
**ZERO G**



**18.9000.8812/79.M9000**

---

**CASE, DIAL & HANDS**

Hour-markers	Gold-plated, faceted and coated with black SuperLuminova SLN [Hour markers]
Hands	Gold-plated, faceted and coated with SuperLuminova SLN C1 [Hands]

---

**STRAPS & BUCKLES**

Bracelet	reference: 27.18.9000.9004 designation: Rose gold bracelet interhorn: 23/22 abbreviation: MT XL size: False XS size: False
----------	---