

DEFY
ZERO G



18.9000.8812/79.R584

MODEL SPECIFICATIONS

KEY POINTS

New entirely skeletonised movement : El Primero 8812 S
 "Gravity Control" gyroscopic module that ensures horizontal positioning of the regulating organ
 Now occupies only 30% of its initial volume
 Inspired by the legendary marine chronometers
 Openworked dial

MOVEMENT

Movement	El Primero 8812 S, Manual
Calibre	16 3/4 ` ` ` (Diameter: 38.5 mm)
Movement thickness	7.85 mm
Components	324
Components 2	Gyroscopic carriage made of 139 components
Jewels	41
Frequency	36,000 VpH (5 Hz)
Power-reserve	min. 50 hours
Finishes	Platinum counterweight of the gyroscopic system

FUNCTIONS

Hours and minutes excentred at 12 o'clock
 Small seconds at 9 o'clock
 Self-regulating Gravity Control module at 6 o'clock
 Power-reserve indication at 2 o'clock

CASE, DIAL & HANDS

Diameter	44 mm
Diameter opening	35.5 mm
Thickness	14.85 mm
Crystal	Domed sapphire crystal with anti-reflective treatment on both sides
Case-back	Transparent sapphire crystal
Material	Rose gold 18-ct Rose Gold
Water-resistance	10 ATM
Dial	Openworked with one different-coloured counter

**DEFY
ZERO G**



18.9000.8812/79.R584

CASE, DIAL & HANDS

Hour-markers	Gold-plated, faceted and coated with black SuperLuminova SLN [Hour markers]
Hands	Gold-plated, faceted and coated with SuperLuminova SLN C1 [Hands]

STRAPS & BUCKLES

Bracelet	reference: 27.00.2322.584 designation: Black Rubber with blue alligator leather coating interhorn: 23/22 strand length: 100/80 abbreviation: AL XL size: True strand length xl: 110/90 XS size: True strand length xs: 90/70
Buckle	27.87.0022.930 Gold & Titanium double folding buckle