

**DEFY**  
**EL PRIMERO 21**



**33.9000.9004/78.R582**

## MODEL SPECIFICATIONS

<b>KEY POINTS</b>		1/100th of a second Chronograph movement Exclusive dynamic signature of one rotation per second 1 escapement for the Watch (36,000 VpH - 5 Hz) ; 1 escapement for the Chronograph (360,000 VpH - 50Hz) Certified Chronometer
<b>MOVEMENT</b>	Movement	El Primero 9004, Automatic
	Calibre	14½` `` (Diameter: 32 mm)
	Movement thickness	7.9 mm
	Components	293
	Jewels	53
	Frequency	36,000 VpH (5 Hz)
	Power-reserve	min. 50 hours
	Finishes	Special oscillating weight with satined finishings
<b>FUNCTIONS</b>		Hours and minutes in the centre Small seconds at 9 o'clock 1/100th of a second Chronograph: - Central chronograph hand - 30-minute counter at 3 o'clock - 60-second counter at 6 o'clock - Chronograph power-reserve indication at 12 o'clock
<b>GEMSETTING</b>	Carats	~2.12 cts
	Bezel	44 WS baguette-cut diamonds
<b>CASE, DIAL &amp; HANDS</b>	Diameter	44 mm
	Diameter opening	35.5 mm
	Thickness	14.50 mm
	Crystal	Domed sapphire crystal with anti-reflective treatment on both sides
	Case-back	Transparent sapphire crystal

**DEFY**  
**EL PRIMERO 21**



**33.9000.9004/78.R582**

---

**CASE, DIAL & HANDS**

Material	Titanium with diamonds Titanium
Water-resistance	10 ATM
Dial	Openworked with two different-coloured counters
Hour-markers	Rhodium-plated, faceted and coated with SuperLuminova SLN C1 [Hour markers]
Hands	Rhodium-plated, faceted and coated with SuperLuminova SLN C1 [Hands]

---

**STRAPS & BUCKLES**

Bracelet	reference: 27.00.2322.582 designation: Black Rubber with black alligator leather coating interhorn: 23/22 strand length: 100/80 abbreviation: AL XL size: True strand length xl: 110/90 XS size: True strand length xs: 90/70
Buckle	27.95.0022.930 Titanium double folding clasp