

DEFY
EL PRIMERO 21



49.9000.9004/78.R782

MODEL SPECIFICATIONS

KEY POINTS		New 1/100th of a second Chronograph movement Exclusive dynamic signature of one rotation per second 1 escapement for the Watch (36,000 VpH - 5 Hz) ; 1 escapement for the Chronograph (360,000 VpH - 50Hz) Certified Chronometer
MOVEMENT	Movement	El Primero 9004, Automatic
	Calibre	14½` `` (Diameter: 32 mm)
	Movement thickness	7.9 mm
	Components	293
	Jewels	53
	Frequency	36,000 VpH (5 Hz)
	Power-reserve	min. 50 hours
	Finishes	Special oscillating weight with satined finishings
FUNCTIONS		Hours and minutes in the centre Small seconds at 9 o'clock 1/100th of a second Chronograph: - Central chronograph hand - 30-minute counter at 3 o'clock - 60-second counter at 6 o'clock - Chronograph power-reserve indication at 12 o'clock
CASE, DIAL & HANDS		
	Diameter	44 mm
	Diameter opening	35.5 mm
	Thickness	14.50 mm
	Crystal	Domed sapphire crystal with anti-reflective treatment on both sides
	Case-back	Transparent sapphire crystal
	Material	Black ceramic Ceramic
	Water-resistance	10 ATM
	Dial	Openworked with two different-coloured counters

DEFY
EL PRIMERO 21



49.9000.9004/78.R782

CASE, DIAL & HANDS	Hour-markers	Ruthenium-plated, faceted and coated with SuperLuminova SLN C1
	Hands	Ruthenium-plated, faceted and coated with SuperLuminova SLN C1
STRAPS & BUCKLES	Bracelet	reference: 27.00.2322.782 designation: Black Rubber (HNBR Quality) interhorn: 23/22 strand length: 100/80 abbreviation: RB XL size: True strand length xl: 110/90 XS size: True strand length xs: 90/70
	Buckle	27.96.0022.930 Titanium double folding clasp with Black DLC coating