

DEFY
EL PRIMERO 21



95.9000.9004/78.R582

MODEL SPECIFICATIONS

KEY POINTS

New 1/100th of a second Chronograph movement
 Exclusive dynamic signature of one rotation per second
 1 escapement for the Watch (36,000 VpH - 5 Hz) ; 1 escapement for the Chronograph (360,000 VpH - 50Hz)
 Certified Chronometer

MOVEMENT

Movement	El Primero 9004, Automatic
Calibre	14½` `` (Diameter: 32 mm)
Movement thickness	7.9 mm
Components	293
Jewels	53
Frequency	36,000 VpH (5 Hz)
Power-reserve	min. 50 hours
Finishes	Special oscillating weight with satined finishings

FUNCTIONS

Hours and minutes in the centre
 Small seconds at 9 o'clock
 1/100th of a second Chronograph:
 - Central chronograph hand
 - 30-minute counter at 3 o'clock
 - 60-second counter at 6 o'clock
 - Chronograph power-reserve indication at 12 o'clock

CASE, DIAL & HANDS

Diameter	44 mm
Diameter opening	35.5 mm
Thickness	14.50 mm
Crystal	Domed sapphire crystal with anti-reflective treatment on both sides
Case-back	Transparent sapphire crystal
Material	Brushed titanium Brushed Titanium
Water-resistance	10 ATM
Dial	Openworked with two different-coloured counters

DEFY
EL PRIMERO 21



95.9000.9004/78.R582

CASE, DIAL & HANDS	Hour-markers	Rhodium-plated, faceted and coated with SuperLuminova SLN C1 [Hour markers]
	Hands	Rhodium-plated, faceted and coated with SuperLuminova SLN C1 [Hands]
STRAPS & BUCKLES	Bracelet	reference: 27.00.2322.582 designation: Black Rubber with black alligator leather coating interhorn: 23/22 strand length: 100/80 abbreviation: AL XL size: True strand length xl: 110/90 XS size: True strand length xs: 90/70
	Buckle	27.95.0022.930 Titanium double folding clasp