

DEFY
EL PRIMERO 21



95.9005.9004/01.M9000

MODEL SPECIFICATIONS

KEY POINTS		New 1/100th of a second Chronograph movement Exclusive dynamic signature of one rotation per second 1 escapement for the Watch (36,000 VpH - 5 Hz) ; 1 escapement for the Chronograph (360,000 VpH - 50Hz) Certified Chronometer
MOVEMENT	Movement	El Primero 9004, Automatic
	Calibre	14½` `` (Diameter: 32 mm)
	Movement thickness	7.9 mm
	Components	293
	Jewels	53
	Frequency	36,000 VpH (5 Hz)
	Power-reserve	min. 50 hours
	Finishes	Special oscillating weight with satined finishings
FUNCTIONS		Hours and minutes in the centre Small seconds at 9 o'clock 1/100th of a second Chronograph: - Central chronograph hand - 30-minute counter at 3 o'clock - 60-second counter at 6 o'clock - Chronograph power-reserve indication at 12 o'clock
CASE, DIAL & HANDS	Diameter	44 mm
	Diameter opening	35.5 mm
	Thickness	14.50 mm
	Crystal	Domed sapphire crystal with anti-reflective treatment on both sides
	Case-back	Transparent sapphire crystal
	Material	Brushed titanium & Black Ceramic bezel Titanium & Ceramic
	Water-resistance	10 ATM
	Dial	Silver-toned brushed dial with black-toned counters

DEFY
EL PRIMERO 21



95.9005.9004/01.M9000

CASE, DIAL & HANDS

Hour-markers	Rhodium-plated, faceted and coated with SuperLuminova SLN C1 [Hour markers]
Hands	Rhodium-plated, faceted and coated with SuperLuminova SLN C1 [Hands]

STRAPS & BUCKLES

Bracelet	reference: 27.95.9000.9004 designation: Titanium Bracelet interhorn: 23/22 abbreviation: MT XL size: False XS size: False
----------	--